



STYLEGUARD-BT

**BARKERS FENCING RAILING SYSTEMS
FOR SCHOOLS, PLAY AREAS, COMMERCIAL BUSINESS & RETAIL OUTLETS**



AVAILABLE FROM STOCK SEE PAGE 6

Standard sizes

Fence height (m)	Embedded length of post	Diameter of vertical round (mm)	Spacing of verticals (centres)	Size of horizontals mm	Size of RSJ post	Size of RHS post
1	450	12	112	30 x 10	100 x 55	50 x 50
1.2	500	12	112	30 x 10	100 x 55	50 x 50
1.2	500	16	112	40 x 10	100 x 55	50 x 50
1.5	550	16	112	40 x 10	100 x 55	50 x 50
1.8	600	20	120	50 x 10	100 x 55	70 x 70
2.4	600	22	120	50 x 10	100 x 55	80 x 80

Bow top railing systems are available in a variety of styles: single, interlaced, bow in bow, bar in bow and bow and bar.

Heights

Produced from solid bar, in all heights up to 3.0m.

Horizontals

Available in flat or channel section.

Posts

Intermediates, Corners and Ends are available in a wide range of sizes and materials including: RHS and IPE, with the provision to be stepped or cranked to suit site conditions, secured in concrete

(supplied complete with optional two support legs per standard panel for concrete-in fixing) or base plated for surface mounting.

All posts are manufactured with welded steel caps and a range of post head details are available for all railings as an optional extra.

Panels

Panels are available as standard to 2.72m wide panels welded in accordance with BS: EN: 1722 Pt9.

Panels can also be made to suit your specific requirements - custom lengths, straight, curved or raked.

Gates

Standard gates are available or tailored-made to suit your requirements. All gates are supplied with adjustable hinges, pad-lockable drop-bolts, multi-holed to suit site conditions and robust pad-lockable slide latches. See our gate range for further details.